

This gym floor seal is formulated with modern polyurethane resins designed to penetrate into and seal the pores of wood surfaces for superior protection.

**DIRECTIONS:**

On previously sealed floors: If desired, apply a paint stripper or varnish remover to remove old finish. All oil, grease, soil and residue of varnish remover must be removed by dry cleaning with a waterless wood floor cleaner and rinsed thoroughly with dry cleaning solvent. Dry overnight or until wood is dry to the touch. Buff with a #120 abrasive screen. Remove all dust by vacuum and follow with tack rag treated with mineral spirits. Then follow directions for seal new or sanded floors.

**NEW OR SANDED FLOORS:** Sweep or vacuum floor and follow with tack rag treated with mineral spirits to pick up dust. Apply this seal with a clean lamb's wool applicator. The first coat should be applied across the grain of the wood, and the second coat should be applied with the grain. A third coat, applied with the grain, may be required for extremely porous wood. Buff lightly with a #120 abrasive screen and wipe with a treated tack rag to remove all dust in preparation for the finish coat. For a compatible high gloss, resilient finish coating, apply GYM FLOOR FINISH.

# 30% GYM FLOOR SEAL

OIL MODIFIED POLYURETHANE  
FOR SEALING WOOD GYM FLOORS  
CONTAINS 30% SOLIDS

FOR A GLOSSY, DURABLE FINISH  
USE GYM FLOOR FINISH AFTER  
SEALING WITH GYM FLOOR SEAL

**CAUTION – COMBUSTIBLE**

Harmful or fatal if swallowed. Keep away from heat or open flame. Vapor harmful. See side panel for further cautions and first aid instructions.

**KEEP OUT OF REACH OF CHILDREN**

Sold By:

**CAUTION – COMBUSTIBLE**

Harmful or fatal if swallowed. Keep away from heat or open flame. Vapor harmful. Do not take internally. Extinguish all sources of ignition in entire building where product is being used. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. In case of spill, soak up with absorbent material and place in closed container for disposal according to environmental regulations. Do not use in the presence of food. In case of fire, use dry chemical, foam or CO2 fire extinguisher. (FORCED VENTILATION SHOULD BE PROVIDED WHEN APPLYING SEALER). If adequate ventilation cannot be provided, applicator must wear a organic vapor respirator approved under NIOSH 23C.

**FIRST AID:**

Ingestion – If swallowed, contact physician or poison control center immediately. Do NOT induce vomiting.

Inhalation – Remove person to fresh air. If irritation and/or breathing difficulty persists, obtain medical attention.

Eyes – Flush with plenty of water for at least 15 minutes and obtain medical attention.

External – Wash with soap and water.

**KEEP OUT OF REACH OF CHILDREN**

12690637

NET CONTENTS:

GALLONS