

**DIRECTIONS FOR USE:**

CHISEL STRIPPER has been carefully formulated to remove heavy accumulations of acrylic, natural or synthetic floor finishes without scrubbing. Dust mop entire floor to remove loose dust and dirt. Prepare a stripping solution by diluting 16 to 32 ounces of CHISEL STRIPPER per gallon of cool water. Recommended dilution rates are based upon floors with an accumulation of 10 coats of applied floor finish. To ensure proper solution strength, apply diluted product to a small area of floor. If stripping solution does not cut through all accumulated finish, add more CHISEL STRIPPER. Flood floor with stripping solution with a wet mop. Allow the stripping solution to remain on the floor for 5 to 10 minutes. Do not allow stripping solution to dry on floor. After 5 minutes, agitate "turn over" stripping solution on with stripping mop. This action puts fresh solution in contact with floor to complete the stripping process. Pick up the stripping/finish residue with a wet vac or autoscrubber. Damp mop floor with clean, cool water and a clean mop.

Hazardous Materials Information System (HMIS)					National Fire Protection Association (NFPA)	
HEALTH	2	Severe	4	Extreme	HEALTH	2
FLAMMABILITY	0	Severe	3	High	FLAMMABILITY	0
REACTIVITY	0	Moderate	2	Moderate	REACTIVITY	0
PERSONAL PROTECTION	0	Slight	1	Slight	SPECIAL PRECAUTIONS	COR
		Minimal	0	Insignificant		

# CHISEL STRIPPER

EFFECTIVE STRIPPING WITHOUT MACHINE SCRUBBING

POTENT FORMULA STRIPS COMPLETELY THE FIRST TIME

**WARNING:** May cause skin and eye irritation. See back panel for additional precautionary statements and first aid instructions.

**KEEP OUT OF REACH OF CHILDREN**

Sold By:

**PROFESSIONAL SECRETS TO EFFECTIVE FLOOR CARE:**

- Stripping solution should always be prepared just prior to use.
- Always dry mop before starting any stripping operation - Unremoved dirt and dust can damage floors during scrubbing operations.
- Use only cool water when diluting CHISEL STRIPPER. Cool water slows down the evaporation of volatile stripping agents to prevent drying on floor.
- Use a small piece of a scrubbing pad or a doodle bug to remove marks.
- Use a separate mop and bucket for stripping and damp mopping operations. Accumulated residues on stripper mop left on floor could prevent bonding of finish coats.

**WARNING: HARMFUL IF SWALLOWED.**

Avoid contact with eyes or mucous membranes. Prolonged or repeated exposure to skin may cause irritation. Use with adequate ventilation. If swallowed, give person large quantities of water and obtain medical assistance. Do NOT induce vomiting. If in eyes, flush with large quantities of cool water for at least 15 minutes. Obtain medical assistance. If in skin, wash with soap and water.

**KEEP OUT OF REACH OF CHILDREN**

171693005

NET CONTENTS: