

CUTTING & TAPPING FLUID

COOLANT & LUBRICANT FOR
DRILLING, TAPPING, CUTTING,
AND ALL MACHINING OPERATIONS

CLINGING FORMULA STAYS ON TOOL!

NET CONTENTS: 12 ounces

CAUTION: CONTENTS UNDER PRESSURE.
VAPOR HARMFUL.

Maybe harmful if swallowed. See side panel for
additional precautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

This synthetic cutting and tapping fluid contains special sulfo-chlorinated extreme pressure additives that will increase production and extend tool life. This high performance product is designed for use with carbon steels, stainless and other hard alloys as well as free machining steels.

This unique clinging formula stays on the cutting tool to provide excellent residual lubrication for cooler tool temperatures, cleaner cuts, smoother finishes. For use in milling, boring, cutting, grinding, tapping, threading, sawing and all machining operations. This versatile fluid allows better workpiece visibility and protection against rust. Not recommended for use on copper or aluminum.

CAUTION: CONTENTS UNDER PRESSURE.

VAPOR HARMFUL. May be harmful if swallowed. Avoid breathing vapors. Use only in well ventilated area. Do not expose to temperatures above 120° F. Do not puncture or incinerate can. Avoid contact with eyes and mucous membranes. Avoid prolonged or repeated contact with skin. If in eyes, flush with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention. If swallowed, give person several glasses of water and call a physician. Do NOT induce vomiting. Wash with soap and water after use.

KEEP OUT OF REACH OF CHILDREN

A10391166

This product contains	CAS #
Trichloroethylene	79-01-6
Carbon Dioxide	124-38-9